

SLIP- ON

SOCKET WELD

BLIND



## DIMENSIONS OF CLASS 150 FLANGES AS PER ANSI B16.5

N.B.	A	B	C	D	E	F	G	H	J	K	L	M	N	O	P	R	T	No of Holes
15	89	11.1	1.6	35	16	30	22.4	9.5	21.3	-	48	16	16	23.0	60.3	3.0	15.9	4
20	98	12.7	1.6	43	16	38	27.7	11.0	26.7	-	52	16	16	28.0	69.8	3.0	15.9	4
25	108	14.3	1.6	51	17	49	34.5	12.5	33.4	-	56	17	17	35.0	79.4	3.0	15.9	4
32	117	15.9	1.6	64	21	59	43.2	14.5	42.2	-	57	21	21	43.5	88.9	5.0	15.9	4
40	127	17.5	1.6	73	22	65	49.5	16.0	48.3	-	62	22	22	50.0	98.4	6.5	15.9	4
50	152	19.0	1.6	92	25	78	62.0	17.5	60.3	-	64	25	25	62.5	120.6	8.0	19.0	4
65	178	22.2	1.6	105	29	90	74.7	19.0	73.0	-	70	29	29	75.5	139.7	8.0	19.0	4
80	190	23.8	1.6	127	30	108	90.7	20.5	88.9	-	70	30	30	91.5	152.4	9.5	19.0	4
90	216	23.8	1.6	140	32	122	103.4	-	101.6	-	71	32	32	104.0	177.8	9.5	19.0	8
100	229	23.8	1.6	157	33	135	116.1	-	114.3	-	76	33	33	117.0	190.5	11.0	19.0	8
125	254	23.8	1.6	186	37	164	143.8	-	141.3	-	89	37	37	145.0	215.9	11.0	22.2	8
150	279	25.4	1.6	216	40	192	170.7	-	168.3	-	89	40	40	171.0	241.3	12.5	22.2	8
200	343	28.6	1.6	270	44	246	221.5	-	219.1	-	102	44	44	22.0	298.4	12.5	22.2	8
250	406	30.2	1.6	324	49	305	276.4	-	273.0	-	102	49	49	277.0	362.0	12.5	25.4	12
300	483	31.8	1.6	381	56	365	327.2	-	323.9	-	114	56	56	328.0	431.8	12.5	25.4	12
350	533	34.9	1.6	413	57	400	359.2	-	355.6	-	127	57	79	360.0	476.2	12.5	28.6	12
400	597	36.5	1.6	470	64	457	410.5	-	406.4	-	127	64	87	411.0	539.8	12.5	28.6	16
450	635	39.7	1.6	533	68	505	461.8	-	457.2	-	140	68	97	462.0	577.8	12.5	31.8	16
500	698	42.9	1.6	584	73	559	513.1	-	508.0	-	144	73	103	514.0	635.0	12.5	31.8	20
600	813	47.6	1.6	692	83	664	616.0	-	609.6	-	152	83	111	616.0	749.3	12.5	34.9	20

■ All dimensions are in Millimeters

■ DIMENSIONS AND OTHER SPECIFICATION AS PER CUSTOMERS REQUIREMENTS ARE AVAILABLE ON REQUEST