


FORGED SCREWED FITTING TO ANSI B-16.11, 3000/6000 LBS. THREADED TO ASA B2.1


90° ELBOW TEE 45° ELBOW UNION COUPLING PIPE CAP BUSHING HEX HEAD PLUG



DIMENSION IN MM

NOM BORE	PIPE O.D.	3000 LBS.					COMMON FACTORS						6000 LBS.						
		A	B	C	G	H	K	D	E	F	I	J	L	A	B	C	G	H	K
1/8"	10.3	21	22	17	32	16	19	11	10	40	-	6	-	25	25	19	32	22	-
1/4"	13.7	25	25	19	35	19	25	16	11	43	3	6	32	29	33	22	35	25	27
3/8"	17.2	29	33	22	38	22	25	17.5	13	48	4	8	38	33	38	25	38	32	27
1/2"	21.3	33	38	25	48	29	32	22	15	51	5	8	46	38	46	29	48	38	33
3/4"	26.7	38	46	29	51	35	37	27	16	57	6	10	51	44	56	33	51	44	38
1"	33.4	44	56	33	60	44	41	35	19	64	6	10	60	51	62	35	60	57	43
1 1/4"	42.2	51	62	35	67	57	44	44.5	21	70	7	14	72	60	75	43	67	64	46
1 1/2"	48.3	60	75	43	79	64	44	51	21	79	8	16	80	64	84	44	79	76	48

90° ELBOW TEE 45° ELBOW UNION COUPLING REDUCER / HALF COUPLING CAP



SOCKET WELD FITTING TO ANSI B-16.11

NOM BORE	PIPE O.D.	3000 LBS.							COMMON FACTORS				6000 LBS.						
		A	B	K	J	L	M	N	P	Q	C	D	O	O	A	B	M	K	N
		max.	max.								min.	min.	min.	max.					
1/8"	10.3	22	18.5	26	16	40	17.3	32	17.5	10	10.7	10	5	8	22	22	20	25	46
1/4"	13.7	22	22	26	18	43	21.2	32	17.5	10	14.1	10	5	8	27	25	24	25	51
3/8"	17.2	25	25	26	19	48	25.4	36	19	10	17.6	10	3	9	27	28	28	26	60
1/2"	21.3	27	32	30	21	51	31	43	22	10	21.7	10	6	13	31	34	34	31	72
3/4"	26.7	34	38	36	24	57	37	50	25	13	27	13	6	13	37	42	41	35	80
1"	33.4	37	46	40	25	64	45.2	60	27	13	33.8	13	9	17	42	50	50	40	94
1 1/4"	42.2	42	56	40	29	70	55	70	30	13	42.6	13	9	17	47	59	58	41	100
1 1/2"	48.3	47	62	40	30	79	61.4	78	32	13	48.7	13	9	17	53	67	66	43	122

■ DIMENSIONS AND OTHER SPECIFICATION AS PER CUSTOMERS REQUIREMENTS ARE AVAILABLE ON REQUEST